

AO- 08-1 Fiber Optic Splice Closure



Feather:

AO-08-1 Fiber Optic Splice Closure

Maximum capacity: 96F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.


Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature : -40°C ~ 65°C

Parameters:

Type	AO-08-1
Product size	L:410mm Dia:140mm
Product material	PC(Polycarbonate)
Product weight	Approximately 2.5kgs
Suitable Dia of cable	8-18mm
Fibers/Tray	12 /24F
Max capacity(F)	96F
Carton packing Size	62.5*42*45.5CM
Each packing quantity	6EA



AO-08-2 Fiber Optic Splice Closure



Feather:

AO-08-2 Fiber Optic Splice Closure

Maximum capacity: 48F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.

Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature : -40°C ~ 65°C

Parameters:

Type	AO-08-2
Product size	L:410mm Dia:140mm
Product material	PC(Polycarbonate)
Product weight	Approximately 2.5kgs
Suitable Dia of cable	8-22mm
Fibers/Tray	12 /24F
Max capacity(F)	48F
Carton packing Size	62.5*42*45.5CM
Each packing quantity	6EA



AO-08-3 Fiber Optic Splice Closure



Feather:

AO-08-3 Fiber Optic Splice Closure

Maximum capacity: 60F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.


Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature :-40°C~65°C

Parameters:

Type	AO-08-3
Product size	L:375mm Dia:120mm
Product material	ABS
Product weight	Approximately 2.2kgs
Suitable Dia of cable	8-18mm
Fibers/Tray	12F
Max capacity(F)	60F
Carton packing Size	84*39*38CM
Each packing quantity	8 EA



AO-08-4 Fiber Optic Splice Closure



Feather:

AO-08-4 Fiber Optic Splice Closure

Maximum capacity:144F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.


Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature : -40°C ~ 65°C

Parameters:

Type	AO-08-4
Product size	L:470mm Dia:160
Product material	PC(Polycarbonate)
Product weight	Approximately 3kgs
Suitable Dia of cable	8-18mm
Fibers/Tray	12 / 24F
Max capacity(F)	144F
Carton packing Size	62.5*48*49.5CM
Each packing quantity	6 EA



AO-08-8Fiber Optic Splice Closure



Feather:

AO-08-8 Fiber Optic Splice Closure

Maximum capacity: 96F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.

Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature :-40℃~65℃

Parameters:

Type	AO-08-8
Product size	Long:410mm Diameter:140mm
Product material	PC(Polycarbonate)
Product weight	Approximately 2.5kgs
Suitable Dia of cable	8-18mm
Fibers/Tray	12/24F
Max capacity(F)	96F
Carton packing Size	62.5*42*45.5CM
Each packing quantity	6EA



AO-08-11 Fiber Optic Splice Closure



Feather:

AO-08-8 Fiber Optic Splice Closure

Maximum capacity:48F

Seal way: Rubber ring

The use of high-strength engineering plastic shell that can endure harsh conditions such as vibration, impact, tensile cable distortion and strong temperature changes

The use of reusable components to open seal in order to ensure a good airtight waterproof performance.

Does not require special tools, easy to install and open the duplicate.

The scope of application: aerial, direct-buried, wall-mounting, duct-mounting,

The application of temperature :-40℃~65℃

Parameters:

Type	AO-08-11
Product size	L:410mm Dia:140mm
Product material	PC(Polycarbonate)
Product weight	Approximately 2.5kgs
Suitable Dia of cable	8-20mm
Fibers/Tray	12/24F
Max capacity(F)	48F
Carton packing Size	62.5*42*45.5CM
Each packing quantity	6 EA

